



# ROBERCAR C900 F910 UF920

## F08

VERSIÓN: 220923  
Page: 1/3

### LIQUID COMPOUNDS

#### DEFINITION

The new range of **Liquid polishes ROBERCAR** comprises the following three products:

- **ROBERCAR C900 - High cut liquid compound**

High cut liquid compound ideal for polishing process on fully cured surfaces and high resistance clear coats. It offers an excellence balance between high cutting action and gloss. However, according to the colour of the paint or the quality level required, an additional step with a fine liquid compound is recommended. It can be used by hand to remove superficial scratches.

- **ROBERCAR F910 - Fine cut liquid compound**

Fine cut liquid compound for polishing process on fresh and not fully cured surfaces or as final step after using C900 high cut compound. Removes finer sanding scratches and swirl marks guaranteeing an excellent, homogeneous and high-gloss finish. Versatile, for hand or machine application.

- **ROBERCAR UF920 - Ultra fine polish**

Ultra fine polish suitable for protecting and maintaining the high gloss level achieved after compounding. Removes holograms and leaves a long lasting high gloss shine. Machine or hand application. Extremely easy to be removed by hand once dried.

#### PHYSICAL CHARACTERISTICS

	Robercar C900	Robercar F910	Robercar UF920	
<b>Specific weight:</b>	1,5	1,1	1,0	kg/l at 20°C
<b>VOC:</b>	172	143	130	g/l 2004/42/EC - IIB(e)(840)

#### AUXILIARY PRODUCTS




























ART. Nº	PRODUCT	
64446	MICROFIBER CLOTH polishing wipe 40x40 cm	
64447	WOOL PAD velcro polishing bonnet - 200mm	} 64455 POLISH PAD SOFT velcro backing pad-185mm
64448	WOOL PAD SOFT velcro polishing bonnet - 200mm	
64453	FOAM SOFT velcro polishing foam - 200mm	
64449	WOOL PAD SOFT velcro polishing bonnet - 135mm	} 64454 POLISH PAD velcro backing pad-123mm
64450	FOAM velcro polishing foam - 150mm	
64452	FOAM SOFT velcro polishing foam - 150mm	

#### PROCESSES

All polishing work processes of the surfaces, should follow the following steps:

- STEP 1** analyse the superficial defect as well as the conditions of the surface to be rectified
- STEP 2** surface preparation
- STEP 3** choose a polishing process depending on the preparation and choose the best auxiliary product for each one (bonnet/foam/wipe)

To improve the performance of the ROBERCAR range, it is highly recommended to follow these steps depending on the preparation:

process	preparation	product	step 1 auxiliary*	product	step 2 auxiliary*	product	step 3 auxiliary*
1	< P1500	<b>C900</b> 64613 - 1kg 	foam 64450 - Ø150mm  wool pad soft 64448 - Ø200mm 64449 - Ø135mm 	<b>F910</b> 64614 - 1kg 	foam 64450 - Ø150mm 	<b>UF920</b> 64616 - 1L 	foam soft 64452-150mm  microfibre cloth 64446 - 40x40cm  64453- Ø200mm 
2	>P1500	<b>C900</b> 64613 - 1kg 	foam 64450 - Ø150mm  wool pad soft 64448 - Ø200mm 64449 - Ø135mm 			<b>UF920</b> 64616 - 1L 	foam soft 64452-150mm  microfibre cloth 64446 - 40x40cm  64453- Ø200mm 
3	MICRO ABRASIVES			<b>F910</b> 64614 - 1kg 	foam 64450 - Ø150mm  wool pad soft 64448 - Ø200mm 64449 - Ø135mm 	<b>UF920</b> 64616 - 1L 	foam soft 64452-150mm  microfibre cloth 64446 - 40x40cm  64453- Ø200mm 
4	show - off / holograms					<b>UF920</b> 64616 - 1L 	foam soft 64452-150mm  microfibre cloth 64446 - 40x40cm  64453- Ø200mm 

\* Choosing the recommended auxiliaries will depend on the fastness or the level of the finishing desired

### REMARKS

Before choosing the polishing process is very important to take into account the following factors: kind of pad, curing and colour of the surface.

### SAFETY

Follow instructions of product label. For more information check the Safety Data Sheets. Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

### STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +5°C and +30°C.

### GUARANTEE

One year in unopened original packaging.

*These products are for professional use only. The Safety Data Sheet should be consulted before use and the precautionary warnings on the product packaging should be observed. Its correct use, according to its purpose and respecting its technical and security data, provided in these documents, is the sole and exclusive responsibility of the user. ROBERLO S.A.U declines any liability due to the incorrect use of any product.*

*The information included in this documentation is based on our scientific and technical knowledge on the date of its issuance. ROBERLO S.A.U reserves the right to modify and/or discontinue all or part of the information at any time and without prior notice. It is the user's responsibility to verify the update of the information. The latest version of this document replaces all previous versions.*

*All clauses contained herein apply to any future changes or modifications.  
For any additional technical information please consult with our Customer Service or our Technical Department.*

### SUGGESTION:

**Before polishing it is recommended to clean thoroughly the bonnet or the foam in order to avoid the appearance of circular scratches.**