

Equipment

Designation	Drum size	Elevator height (mm)	Agitator rod length (mm)	Paddle diameter (mm)	cover diameter (mm)	Part number
200L RAM	200 L / 55 Gl	1510 to 2410				151091000
COVER	200 L / 55 Gl				635	154261200
200L AGITATOR	200 L / 55 Gl		800	370		154261300
SUCTION	200 L / 55 Gl					154261400

Accessories

Designation	Part number
2 L.DRUM - OIL HP 150 FOR DIAPHRAGM PUMP & OILER	149990017
DRUM ROLLER PLATE 200 L ONLY	151098100
ARI SUPPLY ASSEMBLY	154261930
SLOTTED PADDLE	154261952
AIR FILTER 1/4	154261996
AIR LUBRICATOR 1/4 + SUPPORT	154261997




CYCLIX 200

Drum Cover Agitators

Airspray / Accessories



AGITATION FOR BEST RESULTS

-  Constant quality of mixed materials
-  Stainless steel wetted parts
-  High ROI - no product loss

Markets



BOND • PROTECT • BEAUTIFY



CYCLIX 200

Drum Cover Agitators

Cyclix gear drive agitators for open top 200 liter (55 gal) drum featuring a stainless steel cover mounted on a single post elevator for quick material changes.

This elevator-agitator for 20-40 to 200 Liter drums features a double-effect jack for a fast lift of a stainless steel cover fitted for a quick material drum change. The cover is equipped with a motorized agitator fitted with blades for low viscosity materials and a full stainless steel rod. The elevator is coming on a large fixing plate which makes it very stable and easy to install in paint kitchens, existing installations or an essential component of new installations



Technical data table


Designation	Value	Unit: metric (US)
Length	950 (37)	mm (in)
Height	1510 (59)	mm (in)
Width	644 (25)	mm (in)
Recommended Fluid Pressure	60 (140)	bar (psi)
Rotation Speed	150	1/mn (rpm)
Torque at 100 rpm	34	Nm
Maximum Air Consumption	43	m3/h (cfm)
Maximum Pressure	6.9	bar (psi)
Max power	0.75	kW
Stopping torque	37	Nm



Technologies



Airmix® spray technology



Electrostatic



Airless® spray technology



Airspray Conventional



Description

Performance

- ◆ Bi-directional jack for fast lift of stainless steel agitator cover (3 positions available)
- ◆ Quick material change
- ◆ Stainless Steel slotted paddle impeller for high viscosity materials
- ◆ Lubricated air motor - compact with adjustable speed and safe operation

Productivity

- ◆ User-friendly
- ◆ Agitator disengaged during elevator movement

Sustainability

- ◆ Stainless steel cover is compatible for all materials
- ◆ Suction and return tubes benefit suitable for re-ciculating

